

Home Specifications

Two Storey Homes

kookaburrahomes.com.au

Our Home Specifications - Classic Homes



Fixed price contract 3 month maintenance period Council application and building fees Working drawings, soil report and contour plans Wind speed rated up to N3 (4Im/s) Mains electrical connection - up to 15 metres Sewers and drain connections - up to 30 metres Downpipes from gutter terminated at floor level Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement cladding	PLANNING AND GENERAL WORKS	lifestyle Spec
Council application and building fees Working drawings, soil report and contour plans Wind speed rated up to N3 (41m/s) Mains electrical connection - up to 15 metres Sewers and drain connections - up to 30 metres Downpipes from gutter terminated at floor level Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification OMPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Fixed price contract	~
Working drawings, soil report and contour plans Wind speed rated up to N3 (41m/s) Mains electrical connection - up to 15 metres Sewers and drain connections - up to 30 metres Downpipes from gutter terminated at floor level Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification OMPA concrete Termite treatment collars to slab penetrations Engineered footing design 7 7200mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 2.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	3 month maintenance period	✓
Wind speed rated up to N3 (41m/s) Mains electrical connection - up to 15 metres Sewers and drain connections - up to 30 metres Downpipes from gutter terminated at floor level Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceillings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Council application and building fees	√
Mains electrical connection - up to 15 metres Sewers and drain connections - up to 30 metres Downpipes from gutter terminated at floor level Alains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Working drawings, soil report and contour plans	✓
Sewers and drain connections - up to 30 metres Downpipes from gutter terminated at floor level Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Wind speed rated up to N3 (41m/s)	√
Downpipes from gutter terminated at floor level Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Mains electrical connection - up to 15 metres	✓
Mains water connection from meter - up to 15 metres Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings 42 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Sewers and drain connections - up to 30 metres	✓
Two garden taps on house outside wet areas FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings 42 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Downpipes from gutter terminated at floor level	✓
FOOTINGS AND FOUNDATIONS Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 2.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Mains water connection from meter - up to 15 metres	✓
Siteworks up to 300mm Crossfall Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings 42 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Two garden taps on house outside wet areas	✓
Footings included to 'S' Class classification 20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings 412 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves FATERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	FOOTINGS AND FOUNDATIONS	
20 MPA concrete Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves Panelized Colorbond horizontal cladding or James Hardie fibre cement	Siteworks up to 300mm Crossfall	\checkmark
Termite treatment collars to slab penetrations Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves FATERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Footings included to 'S' Class classification	✓
Engineered footing design FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	20 MPA concrete	✓
FRAME CONSTRUCTION 2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Termite treatment collars to slab penetrations	✓
2700mm high ceilings H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves FXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Engineered footing design	✓
H2 Termite Resistant Timber Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves FXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	FRAME CONSTRUCTION	
Trenched top and bottom plates Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	2700mm high ceilings	\checkmark
Engineered timber frames and trusses FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	H2 Termite Resistant Timber	✓
FLOOR CONSTRUCTION - Upper Level 19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Trenched top and bottom plates	\checkmark
19mm tongue and groove particle board flooring - Termiflor ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Engineered timber frames and trusses	\checkmark
ROOF COVER Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	FLOOR CONSTRUCTION - Upper Level	
Colorbond fascia, gutters and roof sheeting 22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	19mm tongue and groove particle board flooring - Termiflor	\checkmark
22.5 degree pitch 450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	ROOF COVER	
450mm wide eaves EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	Colorbond fascia, gutters and roof sheeting	\checkmark
EXTERNAL CLADDING Panelized Colorbond horizontal cladding or James Hardie fibre cement	22.5 degree pitch	✓
Panelized Colorbond horizontal cladding or James Hardie fibre cement	450mm wide eaves	✓
	EXTERNAL CLADDING	
	•	✓
Painted James Hardie Axent trim to all windows and doors √	Painted James Hardie Axent trim to all windows and doors	\checkmark
INSULATION	INSULATION	
External walls R2.5HD	External walls	R2.5HD
Ceiling: R4 insulation batts	Ceiling: R4 insulation batts	\checkmark
Sisalation foil to external walls	Sisalation foil to external walls	\checkmark
BALCONY	BALCONY	
Stainless steel posts and handrails with stainless steel wire	Stainless steel posts and handrails with stainless steel wire	√
CCA decks and verandah under main roof	CCA decks and verandah under main roof	\checkmark

Our Home Specifications - Classic Homes

Powder coated aluminium sliding windows with fly screens Locks to all windows Obscure glass to bathroom, ensuite and WC LININGS	
Locks to all windows Obscure glass to bathroom, ensuite and WC ✓	
Obscure glass to bathroom, ensuite and WC	
Walls and celing 10mm plasterboard ✓	
55mm cornice	
Three coat wash and wear paint to internal walls	
JOINERY	
Architraves: 67 x 18mm single beveled MDF - painted	
Skirtings: 67 x 18mm single beveled MDF - painted	
Linen cupboard: 4 x melamine shelves	
Polytec Melamine linen doors in Texture, Matt, Finegrain, Sheen, Woodmatt or Ashgrain finish	
Walk In Robe: Melamine shelf and hanging rail	
Shelf bank to Walk In Robe	
Built In Robes	
DOORS AND FURNITURE	
Entry/External: powder coated sliding door with screen or panel carved hinged door	
Internal: flush panel	
Furniture: lever door handles	
ELECTRICAL	
Up to 30 LED downlights to internal area (design specific)	
Light and double powerpoint per room	
2 x double powerpoints to kitchen	
Single powerpoint to fridge	
Smoke detectors hard wired battery backup	
2x TV Point and 2x Phone Point	
External power points to HWS and pump	
External lights to exits	
Earth leakage safety switch √	
TILING	
Kitchen: 600mm splashback	
Bathroom / ensuite: 2100mm to shower, 600mm above bath	
Bathroom / ensuite: 1200mm around walls	
WC: Up to 300mm skirting row around walls	
Laundry: Up to 300mm splashback, Up to 300mm skirting row around walls	
Floor tiles to wet areas laid on square	

Our Home Specifications - Classic Homes

LAUNDRY	lifestyle Spec
45L stainless steel trough with 800mm wide melamine cabinet & laminate benchtop	✓
Tapware from builders range in chrome or matte black	\checkmark
1/4 Turn washing machine taps	\checkmark
KITCHEN	
1 ¾ bowl stainless steel sink with kitchen flickmixer in chrome or matte black	✓
Top of the range Blum motion soft close doors and drawer	✓
Set of 4 Cutlery Drawers	✓
Handles from Builders Range	✓
Stainless steel under bench oven and cooktop	✓
Stainless steel rangehood	✓
Stainless steel dishwasher	✓
Overhead cupboards to fridge and cooktop run. 720mm high with bulkhead	✓
Laminate bench tops	✓
Polytec Melamine doors and drawers in Texture, Matt, Finegrain, Sheen, Woodmatt or Ashgrain finish	✓
Pantry: 4 x melamine shelves	✓
BATHROOM AND ENSUITE	
Vanity cupboard with drawer set	✓
Polytec Melamine vanity doors and drawers in Texture, Matt, Finegrain, Sheen, Woodmatt or Ashgrain finish	√
Acrylic bath approximately 1500mm	✓
Quality tapware from builders range in chrome or matte black	✓
Dual flush porcelain toilet suites	✓
Chrome or matte black accessories	✓
Shower screens: laminated clear glass, semi-frameless surround	✓
Tiled shower base	✓
Mirrors with polished edge - up to 900mm	✓
3 in 1 exhaust / heat / fan	✓
M26 Instantaneous gas HWS for multiple bathroom designs	✓
Pop up wastes to vanity basins	\checkmark



Our Home Specifications - Brick Homes

	10 - 1 0
PLANNING AND GENERAL WORKS	lifestyle Spec
Fixed price contract	√
3 month maintenance period	✓
Council application and building fees	✓
Working drawings, soil report and contour plans	✓
Mains electrical connection - up to 15 metres	√
Sewers and drain connections - up to 30 metres	√
Downpipes from gutter terminated at floor level	✓
Mains water connection from meter - up to 15 metres	✓
Two garden taps on house outside wet areas	✓
FOOTINGS AND FOUNDATIONS	
Siteworks up to 300mm Crossfall	\checkmark
Footings included to 'S' Class classification	\checkmark
20 MPA concrete	\checkmark
Termite treatment collars to slab penetrations	\checkmark
Engineered footing design	\checkmark
FRAME CONSTRUCTION	
2700mm high ceilings	\checkmark
H2 Termite Resistant Timber	\checkmark
Trenched top and bottom plates	✓
Engineered timber frames and trusses	\checkmark
FLOOR CONSTRUCTION - Upper Level	
19mm tongue and groove particle board flooring - Termiflor	\checkmark
ROOF COVER	
Colorbond fascia, gutters and roof sheeting	\checkmark
22.5 degree pitch	\checkmark
450mm wide eaves	\checkmark
BRICK WORK - Lower Level	
Clay Bricks - builders range	\checkmark
Mortar: grey or cream	\checkmark
Joints: raked	\checkmark
EXTERNAL CLADDING - Upper Level	
Texturecoat finish foam panel	\checkmark
INSULATION	
External walls	R2.5HD
Ceiling: R4 insulation batts	\checkmark
Sisalation foil to external walls	\checkmark
BALCONY (design specific)	
Stainless steel posts and handrails with stainless steel wire	\checkmark
Tiled balcony	\checkmark

Our Home Specifications - Brick Homes

WINDOWS	lifestyle Spec
Powder coated aluminium sliding windows with fly screens	✓
Locks to all windows	√
Obscure glass to bathroom, ensuite and WC	√
LININGS	
Walls and celing 10mm plasterboard	✓
55mm cornice	✓
Three coat wash and wear paint to internal walls	✓
JOINERY	
Architraves: 67 x 18mm single beveled MDF - painted	✓
Skirtings: 67 x 18mm single beveled MDF - painted	✓
Linen cupboard: 4 x melamine shelves	✓
Polytec Melamine linen doors in Texture, Matt, Finegrain, Sheen, Woodmatt or Ashgrain finish	✓
Walk In Robe: Melamine shelf and hanging rail	✓
Shelf bank to Walk In Robe	✓
Built In Robes	✓
DOORS AND FURNITURE	
Entry/External: powder coated sliding door with screen or panel carved hinged door	✓
Internal: flush panel	✓
Furniture: lever door handles	✓
ELECTRICAL	
Up to 30 LED downlights to internal area (design specific)	V
Light and double powerpoint per room	✓
2 x double powerpoints to kitchen	✓
Single powerpoint to fridge	V
Smoke detectors hard wired battery backup	✓
2x TV Point and 2x Phone Point	✓
External power points to HWS and pump	✓
External lights to exits	✓
Earth leakage safety switch	✓
TILING	
Kitchen: 600mm splashback	✓
Bathroom / ensuite: 2100mm to shower, 600mm above bath	✓
Bathroom / ensuite: 1200mm around walls	✓
WC: Up to 300mm skirting row around walls	✓
Laundry: Up to 300mm splashback, Up to 300mm skirting row around walls	✓
Floor tiles to wet areas laid on square	✓

Our Home Specifications - Brick Homes

LAUNDRY	lifestyle Spec
45L stainless steel trough with cabinet	✓
Tapware from builders range in chrome or matte black	✓
¼ Turn washing machine taps	✓
KITCHEN	
1 3/4 bowl stainless steel sink with kitchen flickmixer in chrome or matte black	✓
Top of the range Blum motion soft close doors and drawer	✓
Set of 4 Cutlery Drawers	✓
Handles from Builders Range	✓
Stainless steel under bench oven and cooktop	✓
Stainless steel rangehood	✓
Stainless steel dishwasher	✓
Overhead cupboards to fridge and cooktop run. 720mm high with bulkhead	✓
Laminate bench tops	✓
Polytec Melamine doors and drawers in Texture, Matt, Finegrain, Sheen, Woodmatt or Ashgrain finish	√
Pantry: 4 x melamine shelves	✓
BATHROOM AND ENSUITE	
Vanity cupboard with drawer set up to 900mm, powder room wall to wall	✓.
Polytec Melamine vanity doors and drawers in Texture, Matt, Finegrain, Sheen, Woodmatt or Ashgrain finish	J
Acrylic bath approximately 1500mm	V
Quality tapware from builders range in chrome or matte black	V
Dual flush porcelain toilet suites	V
Chrome or matte black accessories	V
Shower screens: laminated clear glass, semi-frameless surround	V
Tiled shower base	V
Mirrors with polished edge - up to 900mm	✓
3 in 1 exhaust / heat / fan	✓
M26 Instantaneous gas HWS	✓
Pop up wastes to vanity basins	✓
GARAGE	
Walls and ceilings 10mm plasterboard	V
Concrete slab	✓
Panel lift door	Automatic with remotes

MURRAY BRIDGE

Design HQ 133 Adelaide Road, Murray Bridge

MOUNT BARKER

The Bridgehampton Display Home Lilac Parade, Clover Park, Mount Barker



1300 000 228 kookaburrahomes.com.au facebook.com/kookaburrahomes instagram.com/kookaburrahomes